

Power Requirements:

Reference

Machine	Heater Power	Facer Power	Hydraulic	Minimum Requirements at Sea Level
MiniMc™	300 Watt @ 120VAC, 1Ph	Hand Operated	None	0.3 KW @120VAC
No.2LC/No.2CU	800 Watt @ 120VAC, 1Ph	Hand Operated	None	0.8 KW @ 120VAC
Socket Fusion	2" – 800 Watt @ 120VAC, 1Ph 4" – 1,200 Watt @ 120VAC, 1Ph	Not Applicable	None	2" Heater – 0.8 KW @ 120VAC 4" Heater – 2.5 KW @ 120VAC
No.14 PitBull®	1,200 Watt @ 120VAC, 1Ph	7 Amps @120VAC (Running) 22 Amps @ 120VAC (Stall)	None	2.5 KW @ 120VAC
Sidewinder™	2" – 800 Watt @ 120VAC, 1Ph 4" – 1,200 Watt @ 120VAC, 1Ph	Not Applicable	None	2" Heater – 0.8 KW @ 120VAC 4" Heater – 2.5 KW @ 120VAC
TracStar® No.28 TracStar No.28CU	1,750 Watt @ 120VAC, 1Ph Sidewall – 2,270 Watt @ 240VAC	Hydraulic	Self-Contained	Self-Contained Gasoline
No.28/250	1,750 Watt @ 120VAC, 1Ph	Hydraulic	1½ HP, 1Ph @ 120VAC	3.5 KW @ 120VAC
No.28CU/ 250CU	1,750 Watt @ 120VAC, 1Ph Sidewall – 2,270 Watt @ 240VAC	Hydraulic	1½ HP, 1Ph @ 120VAC	4 KW @ 120VAC
PitBull® No.28	1,750 Watt @ 240VAC, 1Ph	Hydraulic	5 HP, 3Ph, @ 240VAC	6KW @ 240VAC
TracStar 250 TracStar 250CU	3,000 Watt @ 240VAC, 1Ph Sidewall – 2,270 Watt @ 240VAC	Hydraulic	Self-Contained	Self-Contained Gasoline
PitBull® 250	3,000 Watt @ 240VAC, 1Ph	Hydraulic	5 HP, 3Ph, @ 240VAC	7 KW @ 240VAC
TracStar® No.412	3,000 Watt @ 240VAC, 1Ph	Hydraulic	Self-Contained	Self-Contained, Diesel
No.412	3,000 Watt @ 240VAC 1Ph	Hydraulic	Self-Contained	Self-Contained, Gasoline
No.412E	3,000 Watt @ 240VAC, 1Ph	Hydraulic	3 HP, 3Ph, @ 240VAC	5.5 KW/6.5 KVA @240VAC 60Hz
PitBull® No.412	3,000 Watt @ 240VAC, 1Ph	Hydraulic	5 HP, 3Ph, @ 240VAC	7 KW @ 240VAC
TracStar® No.618	3,000 Watt @ 240VAC, 1Ph	Hydraulic	Self-Contained	Self-Contained, Diesel
No.618	3,000 Watt @ 240VAC, 1Ph	Hydraulic	Self-Contained	Self-Contained, Gasoline
No.618E	3,000 Watt @ 240VAC, 1Ph	Hydraulic	5 HP, 3Ph, @ 240VAC	6.5 KW/7.5 KVA @240VAC 60Hz
PitBull® No.618	3,000 Watt @ 240VAC, 1Ph	Hydraulic	5 HP, 3Ph, @ 240VAC	7 KW @ 240VAC
TracStar® 500 II	4,000 Watt @ 240VAC, 1Ph	Hydraulic	Self-Contained	Self-Contained, Diesel
PitBull® 500 II	4,000 Watt @ 240VAC, 1Ph	Hydraulic	5 HP, 3Ph, @ 240VAC	8KW @ 240VAC
No.824	10,950 Watt @ 240VAC, 3 Ph	Hydraulic	7.5 HP, 3Ph, @ 240VAC	17.5 KW/20 KVA @240VAC 60Hz
TracStar® 900	20,461 Watt @ 240VAC, 3 Ph	Hydraulic	Self-Contained	Self-Contained, Diesel
No.1236	20,461 Watt @ 240VAC, 3 Ph	Hydraulic	10 HP, 3Ph, @ 240VAC	30 KW/30 KVA @240VAC 60Hz
No.1648	35,000 Watt @ 240VAC, 3 Ph	Hydraulic	10 HP, 3Ph, @ 240VAC	50 KW/50 KVA @240VAC 60Hz
No.2065	65" – 38,437 Watt @ 240VAC, 3 Ph 48" – 35,000 Watt @ 240VAC, 3 Ph	Hydraulic	10 HP, 3Ph, @ 240VAC	50 KW/50 KVA @240VAC 60Hz